



LEDAL

BRIGHT IN POWER.
COMPACT IN SCALE.

KEY SPECIFICATIONS

MOUNTING:	Track 3-phase / 1-phase
SIZE:	ø106 x 123mm
MATERIAL:	Die cast aluminum
BEAM ANGLES:	20° / 30° / 40° / 60°
LUMINOUS FLUX:	up to 5600lm
SYSTEM POWER:	11W - 40W
EFFICIENCY:	up to 164lm/W
CCT:	Single CCT / TW / DTW / Retail
CRI:	>90
PROTECTION:	IP20
COLOUR:	White / Black / Grey



EDDAM

**BRIGHT IN POWER.
COMPACT IN SCALE.**

KEY SPECIFICATIONS

MOUNTING:	Track 3-phase / 1-phase
SIZE:	ø95 x 112mm
MATERIAL:	Die cast aluminum
BEAM ANGLES:	15° / 25° / 45° / 60°
LUMINOUS FLUX:	up to 4150lm
SYSTEM POWER:	11W - 31W
EFFICIENCY:	up to 160lm/W
CCT:	Single CCT / TW / DTW / Retail
CRI:	>90
PROTECTION:	IP20
COLOUR:	White / Black / Grey



LED

BRIGHT IN POWER.
SMALLER BY DESIGN.

KEY SPECIFICATIONS

MOUNTING:	Track 3-phase / 1-phase
SIZE:	ø85 x 104mm
MATERIAL:	Die cast aluminum
BEAM ANGLES:	15° / 25° / 40° / 60° / 65°
LUMINOUS FLUX:	up to 2850lm
SYSTEM POWER:	11W – 19W
EFFICIENCY:	up to 160lm/W
CCT:	Single CCT / TW / DTW / Retail
CRI:	>90
PROTECTION:	IP20
COLOUR:	White / Black / Grey