



SIKADI 220 PE

SIMPLE IN FORM.
PRECISION IN LIGHT.

KEY SPECIFICATIONS

MOUNTING:	Suspended
SIZE:	ø220mm x 241mm
CABLE LENGTH:	3000mm
MATERIAL:	Die cast aluminum
BEAM ANGLES:	20° / 30° / 40° / 60°
LUMINOUS FLUX:	up to 5650lm
SYSTEM POWER:	9.5W - 40W
EFFICIENCY:	up to 165lm/W
CCT:	Single CCT / TW / DTW / Retail
CRI:	>90
PROTECTION:	IP20
COLOUR:	White / Black / Grey

SKAD 160 PE

EFFICIENCY IN SHAPE.
CLARITY IN LIGHT.

LIGHT 4U

KEY SPECIFICATIONS

MOUNTING:	Suspended
SIZE:	Ø160mm x 181mm
CABLE LENGTH:	3000mm
MATERIAL:	Die cast aluminum
BEAM ANGLES:	15° / 25° / 45° / 60°
LUMINOUS FLUX:	up to 3050lm
SYSTEM POWER:	9.5W – 19W
EFFICIENCY:	up to 164lm/W
CCT:	Single CCT / TW / DTW / Retail
CRI:	>90
PROTECTION:	IP20
COLOUR:	White / Black / Grey

LIGHT 4U